Date Issued/Revised: June 23, 2000 Supersedes: October 11, 1999

Section 1: Product and Company Identification

Manufacturer: AMSOIL, Inc. Telephone:

925 Tower Avenue CHEMTREC (Spill Emergency Only): 1-800-424-9300

Superior, WI 54880 Information: 715-392-7101

Section 2: Composition/Information on Ingredients

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)


Acetone CAS# 67-64-1

ACGIH TLV: 750 ppm & OSHA PEL: 1000 ppm

Isopropanol, CAS# 67-63-0

ACGIH TLV: 400 ppm & OSHA PEL: 500 ppm
2-Butoxyethonol Glycol Ether EB, CAS # 111-76-2
ACGIH TLV & OSHA PEL 25 ppm (skin)
Isobutane/PropaneBlend, CAS# Mixture
ACGIH TLV: & OSHA PEL: 800-1000 ppm

*See Section 8 for exposure limits.



POTENTIAL HEALTH EFFECTS: WARNING! Combustible Harmful if swallowed, Eye irritant, Inhalation irritant, May cause skin irritation.

*See Section 11 for toxicological information.

Section 4: First Aid Measures

EYE: Flush with water for 15-20 minutes. Seek immediate medical attention.

SKIN: Wash immediately with soap and water. Immediately remove contaminated clothing and launder

before reuse. Discard shoes and leather articles saturated with the product. Obtain medical

advice if irritation occurs.

INHALATION: Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing

has stopped apply artificial respiration. Get immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. If vomiting does

occur, keep head below hips to reduce risk of aspiration. Get immediate medical

attention.

Section 5: Fire Fighting Measures

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, and alcohol foam and water.

Red Flammability

Blue Yellow Reactivity

1 White Special N/A

Date Issued/Revised: June 23, 2000 Supersedes: October 11, 1999

UNUSUAL FIRE & EXPLOSION HAZARDS: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode if ignited. Thermal decomposition of products may include toxic oxides of carbon, overexposure may cause a health hazard.

FIREFIGHTING EQUIPMENT: Full bunker gear recommended including a positive pressure self-contained breathing apparatus Water may be used to cool and protect exposed material.

Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

Section 7: Handling and Storage

HANDLING: Do not puncture or incinerate can. Do not stick pin, nail, or other sharp object into opening on

top of can. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty

container contains product residue, which may exhibit hazards of product.

STORAGE: Store and use in a cool, dry, well-ventilated areas. Do not store above 120° F. Keep away from

heat or flame.

Section 8: Exposure Controls/Personal Protection

VENTILATION: Use adequate general or local exhaust ventilation to keep airborne concentrations below

exposure limits.

RESPIRATORY: Avoid breathing vapors. Use a NIOSH approved respirator when necessary.

SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.

EYE: Use splash goggles or face shield where splashing is expected or can occur.

EXPOSURE LIMITS: Not Applicable.

Section 9: Physical and Chemical Properties

Physical State	Liquid
Boiling Point	
Freezing/Melting Point	
Vapor Pressure	Not Determined
Vapor Density (Air=1)	Not Determined
Evaporation Rate	Not Determined
Solubility in Water	Soluble
Specific Gravity (Water=1)	0.985
Density, lb./gal	8.21
Volatility (Volume)	
VOC	
pH	
Coefficient of Water/Oil Distribution	Not Determined
Odor	
Odor Threshold	Not Determined
Appearance	Clear Spray

Product Code: SSR, Pure Power Spot and Stain Remover.

Date Issued/Revised: June 23, 2000 Supersedes: October 11, 1999

 Viscosity, cSt @ 100°C
 N/A

 Viscosity, cSt @ 40°C
 N/A

 Viscosity Index
 N/A

Section 10: Stability and Reactivity

STABILITY: Stable and will not react violently with water.

INCOMPATIBILITY: Avoid contact with strong oxidizers, concentrated oxygen, sodium hypochlorite or

Calcium hypochlorite.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION OF PRODUCT: None.

Section 11: Toxicological Information

ACUTE EXPOSURE

Eye Irritation: Moderate to severe corneal injury possible and redness persisting for an extended

period of time, Based on data from components or similar material.

Skin Irritation: Not expected to be a primary skin irritant. Based on data from components or

similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying,

defatting, and cracking of the skin.

Respiratory Irritation: If material is misted or if vapors are generated from heating, exposure may cause

irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed,

respiratory irritation should not be a problem.

CHRONIC EXPOSURE

Chronic Toxicity: No data available to indicate product present at greater than 1.0% are chronic

health hazards.

Carcinogenicity: No data available to indicate product present at greater than 0.1% are a

carcinogenic hazard.

Mutagenicity: No data available to indicate product present at greater than 1.0% present a

mutagenic or genotoxic hazard.

Reproductive Toxicity: No data available to indicate product present at greater than 1.0% present a

reproductive hazard.

Teratogenicity: No data available to indicate product present at greater than 1.0% present a

teratogenic hazards.

ADDITIONAL INFORMATION

Exposure Limits: Not Applicable.

Other: No other health hazards are known.

Product Code: SSR, Pure Power Spot and Stain Remover.

Page 3 of 4

Date Issued/Revised: June 23, 2000 Supersedes: October 11, 1999

Section 12: Ecological Information

No data available on the adverse effects of this product on the environment.

Section 13: Disposal Considerations

Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Dispose of in accordance with all local, state and federal regulations. If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Section 14: Transport Information

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

Section 15: Regulatory Information

U.S. Federal Regulations OSHA	ble ble ble
Reactive HazardRelease of Pressure	No No
Acute Health Hazard Y	No
Section 313 Toxic Chemical2-Butoxyethanol, CAS# 111-76	5-2
U.S. State Regulations California (Prop 65) Does not contain chemicals known to the state of California to cause cancer.	
International Regulations WHMISAll components list	ted

Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.